



JOHN DEERE

ENGINE PERFORMANCE CURVE


Rating: M4 - 610 hp (455 kW) @ 2100 rpm

PowerTech 12.5 L Engine

Model: **6125SFM75**

(Propeller Power is approximately 97% of Crankshaft Power)

Application: Marine



Air Intake Restriction 12 in.H₂O (3 kPa)
 Exhaust Back Pressure 30 in.H₂O (7.5 kPa)

Gross power guaranteed within + or - 5% at SAE J1995 and ISO 8665 conditions:

- 77 °F (25 °C) air inlet temperature
- 29.31 in.Hg (99 kPa) barometer
- 104 °F (40 °C) fuel inlet temperature
- 0.853 fuel specific gravity @ 60 °F (15.5 °C)

Conversion factors:

- Power: kW = hp x 0.746
- Fuel: 1 gal = 7.1 lb, 1 L = 0.85 kg
- Torque: N·m = lb-ft x 1.356

All values are from currently available data and are subject to change without notice.

Notes:

Tier-2 Emission Certifications:

- EPA Commercial Marine (40 CFR Part 94)
- IMO Annex VI
- EU 2004/26/EC

Ref: Engine Emission Label

Certified by:

Jennifer Barrett
 12 April 2007

* Revised Data

Curve: 6125SFM75610M4..... Sheet 1 of 2
 April 2007

Common Specifications:

General Data

Model 6125SFM75
 Number of Cylinders 6
 Bore and Stroke--in.(mm)..... 5.00 x 6.50 (127 x 165)
 Displacement--in³ (L)766 (12.5)
 Compression Ratio 17.0 : 1
 Valves per Cylinder -- Intake / Exhaust 2 / 2
 Firing Order 1-5-3-6-2-4
 Engine Type In-line, 4-Cycle
 Aspiration Turbocharged and Aftercooled
 Aftercooling System Sea Water
 Engine Crankcase Vent System Closed

Physical Data

(Includes Engine, Flywheel Housing, Flywheel & Electrics)
 Length--in.(mm)70.9 (1801)
 Width--in.(mm)40.6 (1032)
 Height (centerline to top)--in.(mm)31.0 (786)
 Height (centerline to bottom)--in.(mm)14.3 (364)
 Weight, dry--lb (kg) estimated3252 (1475)
 Center of Gravity Location
 From Rear Face of Block (X-axis)--in.(mm)16.5 (420)
 Right of Crankshaft (Y-axis)--in.(mm).....5.3 (135)
 Above Crankshaft (Z-axis)--in.(mm).....9.6 (244)
 Max. Allow. Static Bending Moment at Rear Face
 of Flywhl Hsg w/5-G Load--lb-ft (N•m)600 (814)
 Thrust Bearing Load Limit (Forward)--lb (N)1835 (8162)
 Maximum Installed Angle
 Front Up--degrees..... 12
 Front Down--degrees 0

Air System

Minimum Ventilation Area--in² (m²).....344.1 (0.222)
 Maximum Allowable Air Temperature Rise
 Ambient to Engine Inlet--°F (°C)31 (17)
 Engine Air Flow--ft³/min (m³/min) 1278 (36.2)
 Intake Manifold Pressure--psi (kPa).....30 (210)
 Maximum Air Intake Restriction
 Dirty Air Cleaner--in. H₂O (kPa).....25 (6.25)
 Clean Air Cleaner--in. H₂O (kPa)..... 12 (3.0)

Engine Specification Data

Cooling System

Engine Radiated Heat--BTU/min (kW)..... 3307 (58.1)
 Coolant Flow--gal/min (L/min)..... 105 (396)
 Minimum Coolant Fill Rate--gal/min (L/min) 3.2 (12)
 Thermostat Start to Open--°F (°C) 160 (71)
 Thermostat Fully Open--°F (°C)..... 183 (84)
 Maximum Top Tank Temperature--°F (°C)212 (100)
 Minimum Sea Water-to-Boil Temperature--°F (°C) .. 90 (32)
 Recommended Pressure Cap--psi (kPa)..... 15 (100)
 Engine Coolant Capacity--qt (L) 42 (40)

Electrical System

12 Volt 24 Volt

Recommended Battery Capacity
 Cold Cranking Amps @ 32 °F (0 °C)--amp 1800 900
 Max. Starting Circuit Resistance--Ohms.....0.0012 ... 0.002
 Starter Rolling Current @ 32 °F (0 °C)--amp .1280 600

Exhaust System

Exhaust Temperature--°F (°C) 739 (393)
 Exhaust Gas Flow--ft³/min (m³/min)2853 (81)
 Min. Exhaust Pipe Diameter, Dry--in.(mm) 6.0 (152)
 Min. Exhaust Pipe Diameter, Wet--in.(mm) 8.0 (204)
 Max. Allowable Back Pressure--in. H₂O (kPa) 30 (7.5)
 Max. Weight on Turbocharger--lb (kg) 55 (25)

Fuel System

ECU Description John Deere Electronic Control
 Fuel Injection Pump Unit Injectors
 Governor Type Electronic
 Governor Regulation--percent 0 to 5.7
 Total Fuel Flow--lb/hr (kg/hr)..... 322 (146)
 Total Fuel Flow--gal/hr (L/hr)..... 46 (172)
 Min. Rec'd. Fuel Line ID--in.(mm)..... 0.31 (8)
 Min. Rec'd. Fuel Line Size -6
 Fuel Consumption--lb/hr (kg/hr)..... 214 (97)
 Fuel Consumption--gal/hr (L/hr)..... 30 (114)
 Maximum Leak Off Line Pressure--psi (kPa)..... 11.5 (80)
 Max. Fuel Transfer Pump Suction Lift--ft (m) fuel 10 (3)
 Max. Fuel Inlet Restriction--in. H₂O (kPa)-120 (-30.0)
 Max. Fuel Height Above Transfer Pump--ft (m) 10 (3)
 Max. Fuel Inlet Temperature--°F (°C) 194 (90)
 Fuel Filter Size @98% Efficiency--Micron 2

Lubrication System

Oil Pressure @ Rated Speed--psi (kPa)..... 48 (334)
 Oil Pressure @ Low Idle--psi (kPa) 21 (146)

Sea Water System

Sea Water Pump Flow--gal/min (L/min)..... 120 (454)
 Maximum Inlet Restriction--in. H₂O (kPa) 120 (30)
 Maximum Outlet Pressure--psi (kPa)..... 29 (200)
 Maximum Suction Lift--ft (m)..... 10 (3.0)

Performance Data

Rated Power--hp (kW) 610 (455)
 Rated Power (Metric) Fuel @ 77 °F (25 °C)--PS 618.6
 Rated Speed--rpm 2100
 Rated Torque--lb-ft (N•m)..... 1526 (2069)
 Peak Torque--lb-ft (N•m) 1953 (2647)
 Peak Torque Speed--rpm..... 1600
 Torque Rise--percent 27
 Low Idle Speed--rpm 600
 BMEP--psi (kPa) 300 (2067)
 Smoke @ Rated Speed--Bosch No. 0.38

Fuel Consumption for Typical Propeller Curve

Engine rpm	Crank. Power hp (kW)	Crank. Torque lb-ft (N•m)	Prop. Absorption hp (kW)	Prop. Fuel gal/hr(L/hr)
2100	610 (455)	1526 (2069)	610 (455)	31.3 (118.5)
2000	604 (451)	1587 (2152)	527 (393)	27.4 (103.8)
1800	602 (449)	1758 (2383)	384 (287)	19.8 (74.9)
1600	595 (444)	1953 (2647)	270 (201)	14.1 (53.5)
1400	462 (344)	1732 (2349)	181 (135)	9.5 (35.8)
1200	296 (221)	1297 (1759)	114 (85)	6.1 (23.0)

Data based on seawater aftercooled* engine.
 All values at rated speed and power with standard options unless otherwise noted.

* Revised Data
 Curve: 6125SFM75610M4 Sheet 2 of 2
 April 2007